




SOCAY Temperature Senso Power NTC Thermistor MF72-SCN20D-11 20Ω 11mm Wide Resistance Range

Our Product Introduction

for more products please visit us on socaydiode.com

Basic Information

- Place of Origin: Shenzhen, Guangdong, China
- Brand Name: SOCAY
- Certification: UL, REACH, ROHS, ISO
- Model Number: MF72-SCN20D-11
- Minimum Order Quantity: 1000
- Price: USD0.01-0.25/piece
- Packaging Details: Bulk
- Delivery Time: 5-8 work days
- Payment Terms: T/T, Western Union, MoneyGram



Product Specification

- Product Name: NTC Thermistor
- Package Type: Φ11mm
- NTC R25: 20Ω
- I_{max} A : 2A
- Resistance Under Load: 613mΩ
- δ mW/ : 14mW/
- τ Secs. : 52Secs.
- Capacitance: 220μF



More Images



Product Description

SOCAY Power NTC Thermistor MF72-SCN20D-11 20Ω 11mm Wide Resistance Range

DATASHEET: [MF72-SCN20D-11_v2105.1.pdf](#)

1.

Electrical characteristics:

Part Number	Resistance at 25 ±20%	Resistance under Load (mΩ)	Max. Permissible Working Current	Dissipation Factor	Maximum permissible capacitance @240Vac	Thermal Time Constant
	R25(Ω)	(mΩ)	I _{max} (A)	δ(mW/)	C(μF)	τ(Sec.)
MF72-SCN20D-11	20	613	2	14	220	52

2.

Features:	Applications:	Storage Conditions of Products:
Period of Storage: 1 year. 2.Storage Conditions: Storage Temperature: -10 ~ +40 . Relative Humidity:≤ 75%RH. Keep away from corrosive atmosphere and sunlight.	power supply. Adapter. Electric motor. Transformer. Halogen lamp. Projector. Switch mode LED driver circuit.	Operating temperature range: -40~+200 . RoHS & Halogen Free (HF) compliant. Body size: Φ11mm. Cost effective. Radial lead resin coated. Wide resistance range. High power rating.

3.

Part Number Code


MF72 SCN 20D - 11

(1) (2) (3) (4)

- (1) MF72: MF72 Series.
 (2) SCN: Socay NTC.
 (3) 20D: Zero Power Resistance at 25 (R25): 20=20Ω
 (4) Body Size: 11=Φ11mm

4.

Maximum Power Rating(P_{max})



5.Packing:

MF72-SCN20D-11	Quantity (pcs/bag)
----------------	--------------------



L short	1000
L long	500


6.


Reliability		
Item	Test conditions / Methods	Test Result
Tensile Strength of Terminals	Fasten body with a Load Applied to each lead 3.0Kg for 1sec.	No break out and damage
Bending Strength of Terminals	Fixed body hand 1.0kg on one terminal bend 90 then back again oppsite.	No break out and damage
Solder Ability	When the Lead wire was dipped into bath Of $235 \pm 5^{\circ}\text{C}$ for 3 seconds after immersion in 25% rosin flux the solder ability ratio of lead wire surface should more than 95%.	More than 95% solder ability
Temp. Cycle Test	$(-40^{\circ}\text{C} \times \rightarrow +25^{\circ}\text{C} \times 3\text{min}) \times 5\text{Cycles}$ $(-85^{\circ}\text{C} \times \rightarrow +25^{\circ}\text{C} \times 3\text{min}) \times 5\text{Cycles}$	$ \Delta R/R \leq \pm 20\%$
Humidity Test	45°C 95%RH×1000 hours	$ \Delta R/R \leq \pm 20\%$
Load Life	6 AMP×1000 hours	$ \Delta R/R \leq \pm 20\%$
Insulation Test	DC 700V	$R \geq 500\text{M}\Omega$

7.Product Display:










Other Hot Product:

- 1.GDT
- 2.NTC Thermistor
- 3.MOV/MLV
- 4.PPTC Fuse
5. TVS Diodes
- 6.SPG

8.Company Profile:



History of Socay Group



5 invention patents

42 utility model patents

16 Design patent





9.Shipping:



FAQ:

Q: May we get some samples?

A: Of course, samples are available.

Q: What is product lead time?

For GDT, TVS, and ESD, the lead time will 1-2 weeks. For TSS, MOV, MLV, NTC, and PPTC, the lead time 2-3 weeks. According your specific requirements, we will further confirm the accurate lead time.

Q: Do you support customization?

A: Of course, We do.

Please feel free to contact us if you have any question.

Contact Person: Aria Wei

Tel/WhatsApp/Wechat/Skype: +8615778830733

Email Address: sc72@socay.com

Website: www.socay.com / www.socay.en.alibaba.com

Address: Floor 4, Building C, Hengxing Science park, No.19 Minqing Road, Longhua District, Shenzhen



Shenzhen Socay Electronics Co., Ltd.



+8618126201429



sylvia@socay.com



socaydiode.com

4/F, Block C, HeHengXing Science & Technology Park, 19 MinQing Road, LongHua District, Shenzhen City,
GuangDong Province, China